

# DPX™-IS 250 isolating switches

63 to 250 A



Dimensions **see e-catalogue**  
Electrical characteristics **p. 170**

Isolating switches for on-load circuit breaking by visible isolation and positive action of the contacts  
Padlock integrated in the handle  
Connection with cage terminals  
Supplied with terminal shields  
Conform to IEC 60947-3  
Category of use AC 23 A  
Accept electrical auxiliaries (p. 169)  
Can be mounted on rail or on plate in XL<sup>3</sup> enclosures

Pack	Cat.Nos		DPX-IS with release
			Can be associated with a residual current relay with separate coils (p. 155), supplied without shunt trip
	3P	4P	<b>Front handle</b>
1	0 266 30	0 266 34	63 A
1	0 266 31	0 266 35	100 A
1	0 266 32	0 266 36	160 A
1	0 266 33	0 266 37	250 A
			<b>Right-hand side handle</b>
1	0 266 40	0 266 44	63 A
1	0 266 41	0 266 45	100 A
1	0 266 42	0 266 46	160 A
1	0 266 43	0 266 47	250 A
			<b>Left-hand side handle</b>
1	0 266 50	0 266 54	63 A
1	0 266 51	0 266 55	100 A
1	0 266 52	0 266 56	160 A
1	0 266 53	0 266 57	250 A

Pack	Cat.Nos		DPX-IS without release
			<b>Front handle</b>
1	3P	4P	0 266 02   0 266 06
1			0 266 03   0 266 07
			<b>Right-hand side handle</b>
1			0 266 12   0 266 16
1			0 266 13   0 266 17
			<b>Left-hand side handle</b>
1			0 266 22   0 266 26
1			0 266 23   0 266 27

Pack	Cat.Nos	Mounting on rail
1	0 262 39	<b>Rail  fixing plate</b> For DPX-IS 250

Pack	Cat.Nos	Rotary handles
1	0 266 89	<b>Direct for emergency use</b> For mounting instead of standard handle Front and right-hand side handle
1	0 266 90	Left-hand side handle
		<b>Vari-depth handle IP 55</b> Comprising: connecting rod, bracket, self-adhesive drilling template, fixing accessories (seal to maintain the IP protection up to IP 55, door lock mechanism)
1	0 266 86	For front and side handle device for emergency use
1	0 266 87	To be ordered with Cat.Nos 0 266 89 or 0 266 90

Pack	Cat.Nos	Accessories
1	0 262 88 <sup>1</sup>	<b>Cage terminals</b> Set of 4
1	0 273 22	<b>Spreaders</b> Set of upstream and downstream spreaders
		<b>Rear terminals</b> Used to convert the fixed version with front terminals to the fixed version with rear terminals
1	3P   4P 0 265 10   0 265 11	Set of upstream and downstream rear terminals
1	0 262 87	<b>Terminal shields</b> Set of 2
1	0 266 92	<b>Padlock</b> For locking mechanism in open position (factory assembled) Padlock with flat key N° ABA90GEL6149
1	0 266 94	<b>Interlock</b> Provides closing of 2 devices at the same time (factory assembled)

<sup>1</sup>: Can not be mounted on side by side mounted earth leakage modules 160 A

For detailed dimensions, **see e-catalogue**



XL<sup>3</sup> mounting accessories, **p. 269**

