



Product description:

FFKu-EL-F is a light corrugated PVC-U conduit, non-flame propagating, in beige.

This corrugated plastic conduit is used for light duty concealed and cavity wall installations.



VDE 0605
DIN EN 61386-22
minimum compressive strength: 320 N/5 cm



Special features

This light duty electrical conduit must not be installed in concrete.

Cat. No.:	Type	Inside Ø mm	Outside Ø mm	Content	PU	Weight PU/kg	Pallet content m	Bend radius > mm
250 10 016	16	11	16	100	m	3,300	2.400	60
250 10 020	20	14,5	20	100	m	4,300	2.000	80
250 10 025	25	18,8	25	50	m	2,650	1.000	100
250 10 032	32	24,5	32	50	m	4,350	800	130
250 10 040	40	31,7	40	25	m	2,875	400	170
250 10 050	50	40,3	50	25	m	4,125	400	220
250 10 063	63	50,7	63	25	m	5,250	150	250

Classification	Code	Meaning	Classification	Code	Meaning
Compressive strength	2	light (320 N)	Protection against solids	4	Foreign matter >= 1.0 mm
Impact strength	2	light (1.0 kg/100 mm)	Protection against water	0	Not specified
Minimum temperature	2	- 5 °C	Corrosion protection	0	Not specified
Maximum temperature	1	+ 60 °C	Tensile strength	0	Not defined
Bending behaviour	2	pliable	Fire behaviour	1	Non flame propagating
Electrical characteristics	2	Insulation	Suspended load	0	Not defined

Standardisation

EN 61386-1:2008 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-22:2004 Conduit systems for cable management - Part 22: Particular requirements - Pliable conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

Outside diameter according to DIN EN 60423 / IEC 60423

All dimensions without tolerances are for information only.



Material properties		Fields of application	
Zero halogen	DIN VDE V 0604-2-100	on plaster	• machines
Low smoke	DIN EN 61034-2	under plaster	• hot asphalt
Non-flame propagating	DIN EN 61386-1	• on wood	• under screed
UV-resistant	DIN 53387	underground installation	prefabricated construction
Highspeed		in concrete	• outdoor

Chemical properties	
Resistant to	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, gasoline, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, nitric acid, hydrochloric acid, sulfuric acid, turpentine, detergent
Limitedly resistant to	gaseous dry chlorine
Not resistant to	benzene, beer

Accessories		
Push-fit coupling	RMKu-E	259 30 ...
Push-fit coupling	SMSKu-EZF	259 50 ...
Plug	FRVS-E	259 70 ...
Plug	FWVS-E	259 75 ...
Clamp	clipfix grey	223 70 ...
Threaded connector	FKV-E	259 55 ...

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-22 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123